

RLP/RYP

Surface Mounted Downlight



The RLP-RYP spotlight is designed for surface-mounted applications, offering the same advanced optical performance as the entire RLP series. Its base includes a dedicated space for seamless ceiling installation. Despite being a surface-mounted fixture, it provides full flexibility in directing light to any angle and in any direction.



RAL COLORS
Std.
9016
Opt.
9005
9006

RLP/RYP

IP20  

Code	Beam Angle	Luminous Flux	System Power	Weight
RLP/RYP 10 NB	24°	1.050 lm	10 W	0.93 Kg
RLP/RYP 10 MB	40°	1.000 lm	10 W	0.93 Kg
RLP/RYP 10 WB	60°	1.020 lm	10 W	0.93 Kg
RLP/RYP 15 NB	24°	1.470 lm	15 W	0.93 Kg
RLP/RYP 15 MB	40°	1.415 lm	15 W	0.93 Kg
RLP/RYP 15 WB	60°	1.440 lm	15 W	0.93Kg

Body: Aluminum
Reflector: PC

Driver: Included
Voltage: 220~240 VAC

Color Temperature: 2700-3000-4000-5000-6500K
Led: COB

IP65 TYPE
(Optional)




ACCESSORY
(Honeycomb Louvre)





BOX DIMENSIONS
36x36x13 cm


BOX WEIGHT
1.1kg

NARROW



MEDIUM



WIDE

