





TEKNOLINE

Basic and Trunk

Teknoline is a comprehensive lighting system offering a wide range of optical light distributions to meet all types of applications and requirements — from linear luminaires to spotlights. It integrates cable and trunking systems, automation infrastructure, emergency units, and routing modules within a single platform.

In addition to these features, the system provides high efficiency and performance, significantly reducing operating expenses and initial investment costs. With its easy and practical installation solutions, Teknoline minimizes labor time and overall project costs.

The trunking can be easily installed by pressing the lock on the luminaire body with your finger.





RAL COLORS

Std.

9016

Opt.


9005

9006


TCA

IP20  


Code	Beam Angle	Luminous Flux	System Power	Weight
TCA 150 HE/MB	40°	5.010 lm	43 W	1.5 Kg
TCA 150 HE/WB	60°	4.990 lm	43 W	1.5 Kg
TCA 150 HE/AS	Asymmetric	4.840 lm	43 W	1.5 Kg
TCA 150 HE/DA	Double Asymmetric	4.970 lm	43 W	1.5 Kg
TCA 150 HO/MB	40°	6.730 lm	65 W	1.5 Kg
TCA 150 HO/WB	60°	6.710 lm	65 W	1.5 Kg
TCA 150 HO/AS	Asymmetric	6.540 lm	65 W	1.5 Kg
TCA 150 HO/DA	Double Asymmetric	6.680 lm	65 W	1.5 Kg

Body: Aluminum extrusion**Driver:** Included**Color Temperature:** 3000-4000-5000-6500K**Lens:** PMMA (Vossloh Schwabe or Ledil)**Voltage:** 220~240 VAC**Led:** Mid PowerBOX DIMENSIONS
162x18x13 cmBOX WEIGHT
6.4kg (4pcs in box)


MEDIUM

cd/klm
— C0 - C180 — C90 - C270


WIDE

cd/klm
— C0 - C180 — C90 - C270

ASYMMETRIC

cd/klm
— C0 - C180 — C90 - C270

DOUBLE ASYMMETRIC

cd/klm
— C0 - C180 — C90 - C270

RAL COLORS

Std.
9016

Opt.
9005
9006



TCE

IP20

Code	Beam Angle	Luminous Flux	System Power	Weight
TCE 150 HE/NB	20°	5.990 lm	44 W	1.8 Kg
TCE 150 HE/WB	60°	6.030 lm	44 W	1.8 Kg
TCE 150 HE/VWB	100°	5.910 lm	44 W	1.8 Kg
TCE 150 HE/AS	Asymmetric	5.900 lm	44 W	1.8 Kg
TCE 150 HE/DA	Double Asymmetric	6.040 lm	44 W	1.8 Kg
TCE 150 HO/NB	20°	7.810 lm	62 W	1.8 Kg
TCE 150 HO/WB	60°	7.830 lm	62 W	1.8 Kg
TCE 150 HO/VWB	100°	7.650 lm	62 W	1.8 Kg
TCE 150 HO/AS	Asymmetric	7.670 lm	62 W	1.8 Kg
TCE 150 HO/DA	Double Asymmetric	7.820 lm	62 W	1.8 Kg

Body: Aluminum extrusion






Driver: Included

Color Temperature: 3000-4000-5000-6500K

Lens: PMMA (Vossloh Schwabe or Ledil)

Voltage: 220~240 VAC

Led: Mid Power



BOX DIMENSIONS
162x18x13 cm



BOX WEIGHT
7.5kg (4pcs in box)

