

Basic Batten





Each fixture is designed for one or two T5 or T8 fluorescent lamp for surface mounting that high protection class is not necessary.



In the two-lamp option; steel sheet reflector provides direct light distribution.



(99.9%) pure aluminum reflector option for high ceilings.

Basic Batten

Fixtures

Batten type fixtures represent the keystone of the lighting. These fixtures are designed to aim for using with T5, T8 lamps through their durable, steady housing and easy mounting features. T5 types of Basic Batten Fixtures aim to increase high efficiency and industrial type fixtures that could be used in various places.

BASIC BATTEN FIXTURES / FMS - FMR



FMS



Description

The housings are made of 0.6 mm thick high quality steel.
The housing and the cover can be joined together simply without the use of any tools.

Code

FMS/118	1x18W L	White
FMS/136	1x36W L	White
FMS/236	2x36W L	White
FMS/158	1x58W L	White
FMS/258	2x58W L	White

Lamp

Color


Box Dimensions

Inside box 6 PCS		
FMS/136	175x1270x 95mm	
FMS/236	175x1270x 95mm	
FMS/158	175x1570x 95mm	
FMS/258	175x1570x 95mm	


Weight

FMS/136	1.650 gr	(1PCS)
FMS/236	2.200 gr	(1PCS)
FMS/158	2.200 gr	(1PCS)
FMS/258	3.100 gr	(1PCS)
FMS/136	9.900 gr	(6PCS)
FMS/236	13.500 gr	(6PCS)
FMS/158	15.500 gr	(6PCS)
FMS/258	19.100 gr	(6PCS)

Protection: IP20



cd/klm
—C0-C180 —C90-C270



cd/klm
—C0-C180 —C90-C270

Dimensions



Code	a	b
FMS/118	25 mm	618 mm
FMS/136	25 mm	1228 mm
FMS/158	25 mm	1528 mm
FMS/218	101mm	618 mm
FMS/236	101mm	1228 mm
FMS/258	101mm	1528 mm

FMR



Description

Reflector:
Manufactured with 0.6 mm thick steel sheet and painted with min. 80 micron electrostatic powder paint.

Code

FMR/136	1x36W L	White
FMR/236	2x36W L	White
FMR/158	1x58W L	White
FMR/258	2x58W L	White

Lamp

Color


Box Dimensions

Batten (inside box 6 PCS)		
136-236	175x1270x97 mm	
158-258	175x1570x97 mm	
Reflector (inside box 10 PCS)		
136-236	323x1265x185 mm	
158-258	323x1565x185 mm	

Weight

FMR/136	3.800 gr	(1PCS)
FMR/236	4.350 gr	(1PCS)
FMR/158	4.900 gr	(1PCS)
FMR/258	5.800 gr	(1PCS)



Protection: IP20



cd/klm
—C0-C180 —C90-C270

FMR Fixtures are composed of batten (FMS) and reflector

Dimensions





FMR-YT



Description

Reflector:
Manufactured of high pure (99.9%) and high efficiency aluminum.

Code


FMR-YT/136
FMR-YT/158
FMR-YT/236
FMR-YT/258

Lamp

1x36W L
1x58W L
2x36W L
2x58W L

Color

White
White
White
White



Box Dimensions

Batten (inside box 6 PCS)
136-236 175x1270x97 mm
158-258 175x1570x97 mm
Reflector (inside box 2 PCS)
136-236 540x1250x140 mm
158-258 540x1550x140 mm

Weight

FMR-YT/136 2.425 gr (1PCS)
FMR-YT/236 2.975 gr (1PCS)
FMR-YT/158 3.160 gr (1PCS)
FMR-YT/258 4.060 gr (1PCS)

Protection: IP20

FMR-YT Fixtures are composed of batten (FMS) and reflector

Dimensions

