



Office Lighting

DARKZONE


IP20



LGR60/3




LGR60/2



LGR60/1

Glare is one of the most important lighting criteria in the illumination of places such as offices and laboratories.

Glare can be expressed at technical level by drawing and calculating the mathematical values. To make it easier to understand DarkZone and a similar luminaire are placed next to reduce luminaire efficiency. DarkZone series luminaires are extremely difficult to compete due to the luminaire efficiency up to 105lm/W



Code	Ceiling Type	a	b
LGR 60	Gypsum	595mm	595mm
LGR 60	Clip-In	599mm	599mm
LGR 60	Modular	595mm	595mm

Code	LGR60/3	LGR60/2	LGR60/1
LED	High Efficiency Mid-Power LED		
System Power	35 W		
Light Flux	3.660 lm	3,400 lm	3.150 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	0,6 mm A1 quality DKP sheet steel 80 micron powder paint		
Optic	Cat-1,Cat-2	Cat-1,Cat-2	Cat-1,Cat-2
Reflector	Polycarbonate		
Cooler	Cooling from the body surface		
Colour	White		
Box Dimensions	67x61x8cm		
Weight	3.7kg	2.8kg	1.9kg

