

	KAÇAK AKIM TEST FORMU (LEAKAGE CURRENT TEST FORM)	TARİH : (DATE) 9.12.2020
		RAPOR NO : (REPORT NO) -
ÜRÜN ADI (PRODUCT NAME) : LML / 60 20W (4000K) LED ARMATÜR		
KODU (CODE) : - SİPARİŞ / MPS NO (ORDER NO) : -		
NUMUNE ÜRÜN (SAMPLE PRODUCT) <input type="checkbox"/>	TİP TESTİ (TYPE TEST) <input checked="" type="checkbox"/>	
ARMATÜR ÖZELLİKLERİ (FEATURES OF LUMINAİRE) :		
DRIVER - ON BOARD		
PCB - CEM3 THERMAL		
LED - SAMSUNG LM281B+ SA Bin		
ALÜMİNYUM EXTRUSİYON PROFİL		
PLASTİK EXTRUSİYON GÖVDE + KAPAK		
SINIF-1 / IP-44		
Deney Süresi: 1 dakika (Test Time) (1 minute)	Deney Başlangıcı: 09 : 27 (Beginning Time)	Deney Bitişi: 09 : 28 (Finish Time)
Akım (Current) I (mA) = 0,03 mA		
I ≤ 0,7 mA Armatür deneyi geçmiştir. (Luminaire passed the test) <input checked="" type="checkbox"/>	I > 0,7 mA Armatür deneyde başarısızdır. (Luminaire failed the test) <input type="checkbox"/>	
AÇIKLAMALAR (EXPLANATION)		
İlgili standart maddesi: TS EN 60598-1, Bölüm: 1, Madde: 10.3 Related article of the standard: EN 60598-1, Part: 1, Article: 10.3		
TESTİ YAPAN (TESTER)	ONAYLAYAN (APPROVED BY)	