


Linear Lighting


EOSLED

IP20
IP40 Optional

DFG 20



DFG 50



DFG 80

DFG fixture series, which are the recessed type of EOSLED are produced in different widths. They can be used as a single profile up to approximately 2.5 meters length in linear applications. They can be attached end to end and be used as a continuous light source. Puller ceiling mounting device has been used in order to adhere to the surface of the edge of the frame thoroughly on the ceiling. Light coming from the LED source creates an extremely soft ambiance by passing through the prismatic diffusers.



Code	a	b	c
DFG 20/100	1038mm	35mm	16mm
DFG 20/120	1208mm	35mm	16mm
DFG 20/150	1542mm	35mm	16mm
DFG 50/100	1036mm	73mm	83mm
DFG 50/120	1236mm	73mm	83mm
DFG 50/150	1536mm	73mm	83mm
DFG 80/100	1034mm	95mm	85mm
DFG 80/120	1204mm	95mm	85mm
DFG 80/150	1538mm	95mm	85mm



DFG BP

Code	DFG 20/20 DFG 20/50 DFG 20/100	DFG 50/100 DFG 50/120 DFG 50/150	DFG 80/100 DFG 80/120 DFG 80/150
LED	High efficiency Mid-Power LED		
System Power	2.5 W 7.5 W 15 W	30 W 35 W 45 W	30 W 35 W 45 W
Light Flux	230 lm 700 lm 1300 lm	2.300 lm 2.600 lm 3.400lm	2.800 lm 3.300 lm 4.000 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	Aluminum extrusion body 80 micron electrostatic powder coated with paint.		
Diffuser	Prismatic Opal		
Colour	White or Grey		
Weight	500 gr 600 gr 750 gr	1.900 gr 2.300 gr 2.700 gr	3.400 gr 4.100 gr 5.200 gr

DFG 80

